

TECHNICAL SHEET

768

Dimensions (mm) Width 1400 x Depth 1050 x Height 1500

Weight (kg)

Electric Power (v) 380 Three-phase + Neutral + Ground

Installed Power (kw) Air Pressure Feeding (bar)

6.0

Air Pressure Consumption (liters/min.) Performances

About 450 containers per hour by Single Format. 900 by Double Format. Data are approximate because the actual performances may depend on the container material, the container dimensions, type of food (solid, liquid, creamy, pasty), the degree to compatible to heat sealing between film

material and container material.

768VG

Dimensions (mm) Width 1400 x Depth 1050 x Height 1500

Weight (kg)

Electric Power (v) 380 Three-phase + Neutral + Ground

Installed Power (kw) 5.0 Air Pressure Feeding (bar)

Air Pressure

Consumption (liters/min.)

Performances (Sealing Only)

About 450 containers per hour by Single Format. 900 by Double Format. About 370 containers per hour by Single Performances (M.A.P.)

Format. 740 by Double Format. Data are approximate because the actual performances may depend on the container material, the container dimensions, type of food (solid, liquid, creamy, pasty), the degree of compatibility to heat sealing between film material and container material, the oxygen remaining inside the thermo-welded container after the end of the whole process.

The information shown in this catalogue is not binding. We reserve the right to make improvements or modifications with no obligation of giving prior

PACKAGING MACHINERY ITALY

Strema s.r.l.

Viale del Lavoro, 8

37060 BUTTAPIETRA

VERONA - ITALY

Tel. +39.045.666.1376

Fax +39.045.666.1381 e-mail - strema@brembenet.com

Internet site - www.strema-machines.com

768 & 768VG

Semi-automatic Traysealers by Rotating Table - Bordered Cutting Packaging















